



Pegasus
hydraulics

Pressure gauge
connectors



14



	Product Groups	Page
	Test point connector	14.02
	Test point tee	14.03
	Test point female compression connector	14.04
	Pressure testing hose	14.05
	Pressure gauge adapter	14.06
	Pressure gauge direct connect adapter	14.07

Note: All nuts are supplied unplated.


Test Point Connectors

BOOK INDEX

SECTION INDEX

M16x2 thread

Viton O-ring




Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	M 8 x 1	37	17	O-ring Form A	MAS-M 8x1-or
630	M 10 x 1	37	17	O-ring Form A	MAS-M 10x1-or
630	M 10 x 1	37	17	Soft Sealing Form C	MAS-M 10x1-wd
630	M 12 x 1.5	37	17	Soft Sealing Form C	MAS-M 12x1.5-wd
630	M 14 x 1.5	37	19	Soft Sealing Form C	MAS-M 14x1.5-wd
630	M 16 x 1.5	37	22	Soft Sealing Form C	MAS-M 16x1.5-wd

Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	G 1/8"	37	17	Soft Sealing Form C	MAS-G 1/8"-wd
630	G 1/4"	37	19	Soft Sealing Form C	MAS-G 1/4"-wd
630	G 3/8"	40	22	Soft Sealing Form C	MAS-G 3/8"-wd
630	G 1/2"	40	27	Soft Sealing Form C	MAS-G 1/2"-wd

Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	R 1/8" keg	36	17	Thread Form D	MAS-R 1/8"-k
630	R 1/4" keg	36	17	Thread Form D	MAS-R 1/4"-k


Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	1/8" NPT	36	17	Thread Form D	MAS-1/8"-NPT
630	1/4" NPT	37	17	Thread Form D	MAS-1/4"-NPT
630	3/8" NPT	40	19	Thread Form D	MAS-3/8"-NPT
630	1/2" NPT	40	22	Thread Form D	MAS-1/2"-NPT

Form A




O-ring seal on shoulder
to SAE J514

Form C



WD = Viton elastomeric soft seal

Form D



BSP taper or NPT

Test point tee


BOOK INDEX

SECTION INDEX

M16x2 thread

Viton O-ring

Supplied with nuts and rings



Series	Pressure PN	Tube O.D. D	Approx. Dimensions				Part code
			L	H	SW1	SW3	
L	315	6	50.5	49.5	24	14	GMV-L-06
L	315	8	50.5	49.5	24	17	GMV-L-08
L	315	10	52.5	49.5	24	19	GMV-L-10
L	315	12	52.5	49.5	24	22	GMV-L-12
L	315	15	54.5	52.5	30	27	GMV-L-15
L	315	18	56.5	53.5	32	32	GMV-L-18
L	160	22	60.5	55.5	36	36	GMV-L-22
L	160	28	60.5	58.0	41	41	GMV-L-28
L	160	35	68.5	60.5	46	50	GMV-L-35
L	160	42	70.5	65.0	55	60	GMV-L-42

Series	Pressure PN	Tube O.D. D	Approx. Dimensions				Part code
			L	H	SW1	SW3	
S	630	6	54.5	49.5	24	17	GMV-S-06
S	630	8	54.5	49.5	24	19	GMV-S-08
S	630	10	56.5	49.5	24	22	GMV-S-10
S	630	12	56.5	49.5	24	24	GMV-S-12
S	630	14	62.5	51.0	27	27	GMV-S-14
S	400	16	62.5	52.5	30	30	GMV-S-16
S	400	20	68.5	55.5	36	36	GMV-S-20
S	400	25	74.5	58.0	41	46	GMV-S-25
S	400	30	80.5	60.5	46	50	GMV-S-30
S	315	38	91.0	65.0	55	60	GMV-S-38

Test point female compression connector

BOOK INDEX


SECTION INDEX

M16x2 thread

Viton O-ring

for connection to W DIN 3861
compression profile

ISO 8434-1 / DIN 2353



Series	Pressure PN	Tube O.D. D	Thread G	Approx. Dimensions		Part code
				L	SW	
L	315	6	M 12 x 1.5	72	14	VKA-DKOL-06
L	315	8	M 14 x 1.5	58	17	VKA-DKOL-08
L	315	10	M 16 x 1.5	58	19	VKA-DKOL-10
L	315	12	M 18 x 1.5	54	22	VKA-DKOL-12
L	315	15	M 22 x 1.5	57	27	VKA-DKOL-15
L	315	18	M 26 x 1.5	59	32	VKA-DKOL-18
L	160	22	M 30 x 2	60	36	VKA-DKOL-22
L	160	28	M 36 x 2	65	41	VKA-DKOL-28
L	160	35	M 45 x 2	70	50	VKA-DKOL-35
L	160	42	M 52 x 2	71	60	VKA-DKOL-42


Series	Pressure PN	Tube O.D. D	Thread G	Approx. Dimensions		Part code
				L	SW	
S	630	6	M 14 x 1.5	72	17	VKA-DKOS-06
S	630	8	M 16 x 1.5	58	19	VKA-DKOS-08
S	630	10	M 18 x 1.5	58	22	VKA-DKOS-10
S	630	12	M 20 x 1.5	54	24	VKA-DKOS-12
S	630	14	M 22 x 1.5	70	27	VKA-DKOS-14
S	400	16	M 24 x 1.5	55	30	VKA-DKOS-16
S	400	20	M 30 x 2	64	36	VKA-DKOS-20
S	400	25	M 36 x 2	66	46	VKA-DKOS-25
S	400	30	M 42 x 2	70	50	VKA-DKOS-30
S	315	38	M 52 x 2	72	60	VKA-DKOS-38

Pressure testing hose

BOOK INDEX

SECTION INDEX

2 x female swivel M16x2 thread





Pressure PN	Hose DN	Thread	Length L (mm)	Part code
630	02	M 16 x 2	200	SMS-M-16-200
630	02	M 16 x 2	400	SMS-M-16-400
630	02	M 16 x 2	630	SMS-M-16-630
630	02	M 16 x 2	800	SMS-M-16-800
630	02	M 16 x 2	1000	SMS-M-16-1000
630	02	M 16 x 2	1500	SMS-M-16-1500
630	02	M 16 x 2	2000	SMS-M-16-2000
630	02	M 16 x 2	2500	SMS-M-16-2500
630	02	M 16 x 2	3200	SMS-M-16-3200
630	02	M 16 x 2	4000	SMS-M-16-4000

Pressure gauge adapter

BOOK INDEX

SECTION INDEX

M16x2 male thread
 female thread either
 BSP parallel or NPT
 DKRi sealing ring to
 be ordered separately



Pressure PN	Thread		Approx. Dimensions			Part code
	G	G1	H	SW1	SW2	
630	1/4" BSP	M 16 x 2	50	19	19	SMA-20-G 1/4"-V
630	1/2" BSP	M 16 x 2	60	27	19	SMA-20-G 1/2"-V


Pressure PN	Thread		Approx. Dimensions			Part code
	G	G1	H	SW1	SW2	
630	1/4" NPT	M 16 x 2	50	19	19	SMA-20-1/4"-NPT-V
630	1/2" NPT	M 16 x 2	60	27	19	SMA-20-1/2"-NPT-V

Pressure gauge direct connect adapter

BOOK INDEX

SECTION INDEX

M16x2 swivel female thread
 Viton O-ring
 female BSP parallel or NPT



Pressure PN	Thread		Approx. Dimensions		Part code
	G	G1	H	SW1	
630	1/4" BSP	M 16 x 2	41	19	SMD-20-G 1/4"
630	1/2" BSP	M 16 x 2	51	27	SMD-20-G 1/2"

Pressure PN	Thread		Approx. Dimensions		Part code
	G	G1	H	SW1	
630	1/4" NPT	M 16 x 2	41	19	SMD-20-1/4"-NPT
630	1/2" NPT	M 16 x 2	51	27	SMD-20-1/2"-NPT