


Test Point Connectors

BOOK INDEX

SECTION INDEX

M16x2 thread

Viton O-ring




Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	M 8 x 1	37	17	O-ring Form A	MAS-M 8x1-or
630	M 10 x 1	37	17	O-ring Form A	MAS-M 10x1-or
630	M 10 x 1	37	17	Soft Sealing Form C	MAS-M 10x1-wd
630	M 12 x 1.5	37	17	Soft Sealing Form C	MAS-M 12x1.5-wd
630	M 14 x 1.5	37	19	Soft Sealing Form C	MAS-M 14x1.5-wd
630	M 16 x 1.5	37	22	Soft Sealing Form C	MAS-M 16x1.5-wd

Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	G 1/8"	37	17	Soft Sealing Form C	MAS-G 1/8"-wd
630	G 1/4"	37	19	Soft Sealing Form C	MAS-G 1/4"-wd
630	G 3/8"	40	22	Soft Sealing Form C	MAS-G 3/8"-wd
630	G 1/2"	40	27	Soft Sealing Form C	MAS-G 1/2"-wd

Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	R 1/8" keg	36	17	Thread Form D	MAS-R 1/8"-k
630	R 1/4" keg	36	17	Thread Form D	MAS-R 1/4"-k


Pressure PN	Thread G	Approx. Dimensions		Sealing	Part code
		H	SW		
630	1/8" NPT	36	17	Thread Form D	MAS-1/8"-NPT
630	1/4" NPT	37	17	Thread Form D	MAS-1/4"-NPT
630	3/8" NPT	40	19	Thread Form D	MAS-3/8"-NPT
630	1/2" NPT	40	22	Thread Form D	MAS-1/2"-NPT

Form A




O-ring seal on shoulder
to SAE J514

Form C



WD = Viton elastomeric soft seal

Form D



BSP taper or NPT