


Swage Ferrule:

PF-PTFE - Page 2.05



DN	Hose Size		I.D. +/- 0.5	O.D. +/- 0.5	Max. Working Pressure		Min. Bend Radius	Weight	Part code			
mm	dash	in.	mm	mm	bar	P.S.I.	mm	g/m				
05		3/16"	5.0	8.2	240	3480	45	83	Hose PT1W-DN 05			
06		1/4"	6.7	10.0	240	3480	100	126	Hose PT1W-DN 06			
08		5/16"	8.2	11.7	200	2900	120	172	Hose PT1W-DN 08			
10		3/8"	10.3	13.8	175	2530	140	223	Hose PT1W-DN 10			
12		1/2"	13.0	17.0	150	2170	160	293	Hose PT1W-DN 12			
16		5/8"	16.0	20.2	135	1950	190	360	Hose PT1W-DN 16			
19		3/4"	19.0	23.2	110	1590	230	423	Hose PT1W-DN 19			
25		1"	25.4	30.3	80	1160	300	640	Hose PT1W-DN 25			

With flat, thick PTFE-Tube (Heavy Wall)

Reinforcement: One Braid of Stainless Wire - AISI 304

Max. Operating Temperature: -60° to +260°C

The working pressure apply to working temperatures from +20°C to +50°C.